

I CLAIM:

1. A hand winch having a removable sway handle comprising:
a main body having a main axis with a winding drum thereon
for winding a cable, a plurality of ratchet teeth of single
5 direction abutting a lateral side of said winding drum, a
subordinate hook secured to one end thereof and a main hook
including a pulley in rear end connected to said cable which
has a distal portion surrounding said pulley and fastened to
a transverse bar at other end of said main body;

10 a sway handle removably and rotatably secured to the main
axis of said main body having a tongs shaped front portion
composed of a pair of symmetrical prongs each of which has
a concave in fore end, a small hole above the concave, a
circular through hole and a screw hole spacedly formed above
15 the small hole, a check pawl rotatably connected to an axial
rod engageable with said ratchet teeth and a lever positioned
under said check pawl and connected with a spring from one
of said prongs for operating said check pawl;

a pair of elastic members each having an elastic plate
20 including a screw hole adjacent free end respectively engaged
with the screw holes of said prongs and secured by a pair of
screw from inner said of said prongs and cap with an opening
in inner side releasably engaged with the circular through
hole from inner side of said prongs;

25 a pair movable plates rotatably secured to outside of said

prongs by a pair of rivets and each having a though hole in
a center engaged with the small hole of said prongs, a
positioning hole adjacent one end engaged with the caps of
said elastic members and a check slot in other end respectively
5 engaged with said main axis and blocking the concave of said
prongs; and

whereby, press said caps inward to set said movable plates
free to rotate to permit said sway handle readily removes
from said main body.

10

15

20

25